



Technical University of Łódz
Institute of Electronics

Algorithms and Data Structures

IPython

Łódź 2012





IPython – ipython.org

IP[y]: IPython Interactive Computing


[Home](#) · [Download](#) · [Documentation](#) · [Videos](#) · [Wiki](#) · [News](#) · [Citation](#)

IPython provides a rich toolkit to help you make the most out of using Python, with:

- Powerful Python shells (terminal and Qt-based).
- A web-based notebook with the same core features but support for code, text, mathematical expressions, inline plots and other rich media.
- Support for interactive data visualization and use of GUI toolkits.
- Flexible, embeddable interpreters to load into your own projects.
- Easy to use, high performance tools for parallel computing.

To learn more about IPython, you can watch our [videos and screencasts](#), download our [talks and presentations](#), or read our [extensive documentation](#). IPython is open source (BSD license), and is used by a range of [other projects](#); add your project to that list if it uses IPython as a library, and please don't forget to [cite the project](#).

IPython supports Python 2.6 to 2.7 and 3.1 or newer. Our older 0.10 series supports Python 2.5, and can be used with Python 2.4.



Google™ Custom Search ×

MEMORIAL

John Hunter
1968–2012
[J. Hunter Memorial Fund](#)

VERSIONS

Stable
0.13 – June 2012
[Download](#)

Development
pre-0.14
[Github](#)

LINKS

[Issue tracker](#)
[Mailing lists:](#)
 User · Dev
[IRC channel](#)
(Freenode, #ipython)
[Try IPython online](#)



IPython

ENTHOUGHT



Starting PyLab



or...



or... Mac OS



The IPython PyLab environment is shown in a window. It displays the following text:

```
Enthought Python Distribution (4.0.30001) -- http://code.enthought.com
Python 2.5.2 |EPD 2.5.2001| (release25-maint:60919M, Feb 21 2008, 10:31:43) EMSC
v.131B 32 bit (Intel)
Type "copyright", "credits" or "license" for more information.

IPython 0.9.beta -- An enhanced Interactive Python.
?           --> Introduction and overview of IPython's features.
%quickref --> Quick reference.
help       --> Python's own help system.
object?    --> Details about 'object'. ?object also works, ?? prints more.

Welcome to pylab, a matplotlib-based Python environment.
For more information, type 'help(pylab)'.

In [1]: a = arange(100.)
In [2]: plot(a, sin(a*pi/50.))
Out[2]: []


In [3]:
```

IPython has a 'pylab' mode where it imports all of NumPy, Matplotlib, and SciPy into the namespace for you as a convenience. It also enables threading for showing plots.



PyLab – Interactive Python Environment

```
Welcome to pylab, a matplotlib-based Python environment [backend: WXAgg].  
For more information, type 'help(pylab)'.  
  
In [1]: a = arange(100.)  
  
In [2]: plot(a*sin(pi/50))  
Out[2]: []  
  
In [3]: plot(a,a*sin(pi/50))  
Out[3]: []  
  
In [4]: plot(a,sin(a*pi/50))  
Out[4]: []  
  
In [5]:
```



```
x = arange(100.)  
  
plot(x,sin(x*pi/50))  
#Now change display option  
hold(False)  
plot(x,cos(x*pi/50))  
# and  
hold(True)  
plot(x,sin(x*pi/50))  
plot(x,cos(x*pi/50))
```



IPython Introducion

STANDARD PYTHON

In [1]: a=1

In [2]: a

Out [2]: 1

AVAILABLE VARIABLES

In [3]: b = [1,2,3]

Comments # (to the end of the line)

List available variables

In [4]: %whos

Variable	Type	Data/Info
----------	------	-----------

a	int	1
---	-----	---

b	list	n=3
---	------	-----

RESET & RELOAD

Reset user defined variables

In [5]: %reset

Once deleted, variables cannot be recovered. Proceed
(y/[n])? y

Let's check our namespace

In [6]: %whos

Interactive namespace is empty.

WARNING: %reset also removes the names imported by PyLab.

In [7]: plot

NameError: name 'plot' is not defined

Reload

In [8]: %pylab

Welcome to pylab, a matplotlib-based Python environment...



Directory navigation in IPython

Get path to current working directory

In [9]: `pwd`

Out[9]: `u'Users/mk'`

Change directory (note Unix style forward slashes)

In [10]: `cd Desktop/`

Tab completion helps you find and type directory and file names

Check the following commands (with `pwd` command):

- `cd ..`
- `cd`

List directory contents (Unix style, not “dir”)

In [11]: `ls`

Desktop/	Library/	Public/	Documents/	Movies/	Sites/	Downloads/
Music/	mipav/	Dropbox/		Pictures/	mySoft/	



Directory navigation in IPython

#Check following commands:

- `ls -l`
- `ls -a`
- `ls -I`

fill the script with commands (the detailed
explanation will appear during next lectures)

```
import pylab as pl  
import numpy as np
```

Go to the D: drive and create folder:

```
#python_lecture_1_tests
```

```
cd d://
```

```
mkdir python_lecture_1_test
```

```
x = np.arange(100)  
y = np.sin(x*np.pi/50.)  
pl.plot(x,y)
```

```
pl.show()
```

in the IPython terminal write:

```
plot(x,cos(x*pi/50.))
```

edit and run (if exists) or create new script

```
edit test_file_1.py
```

IPython is interactive!!!



Directory navigation in IPython

```
# Run script insight IPython(without editing it)
# Interactive mode
%run test_file_1.py
```

```
# To quit IPython use command
In [12]: quit()
```

```
# Run script from the system level (Windos, Unix, Mac OS)
# Batch mode
# Run system console and write
python test_file_1.py
```



Directory Bookmarks

```
# Bookmark the python_lecture_test directory
```

```
cd python_lecture_test
```

```
#bookmark as some name (alias)
```

```
%bookmark lect1
```

```
# bookmark 2 more folders
```

```
# lists bookmarked directories
```

```
%bookmark -l
```

```
# go easily to bookmarked directory
```

```
# go to home directory cd
```

```
# go to lect1 directory
```

```
cd lect1
```



Function Info and Help

Follow the command '?' to print its documentation

```
>>> squeeze?
```

Remove single-dimensional entries from the shape of an array.

Parameters

a : array_like

Input data.

Returns

squeezed : ndarray

The input array, but with all dimensions of length 1 removed. Whenever possible, a view on `a` is returned.



Function Info and Help

```
# Follow a command with '??' to print its source code
# compare: squeeze? And squeeze??
>>> squeeze??
def squeeze(a):
    """ Remove single-dimensional entries from the shape of an array.

Examples
>>> x = np.array([[[0], [1], [2]]])
>>> x.shape
(1, 3, 1)
>>> np.squeeze(x).shape
(3,) """
try:
    squeeze = a.squeeze
except AttributeError:
    return _wrapit(a, 'squeeze')
return squeeze()
```



Function Info and Help

History command

```
# list previous commands. Use 'magic' % because 'hist' is histogram function in pylab  
%hist
```

Input History

```
# list string from prompt [2]
```

```
In[15] a = 5
```

```
...
```

```
>>> _i15
```

```
>>> u'a = 5'
```

```
# The up and down arrows scroll through your ipython input history
```



IPython magic functions

<http://ipython.org/ipython-doc/dev/interactive/tutorial.html#magic-functions>

```
>>> %lsmagic
```

Available magic functions:

```
%alias %autocall %autoindent %automagic %bookmark %cd %colors %config %cpaste  
%debug %dhist %dirs %doctest_mode %ed %edit %env %fread %fwrite %gui %hist %history  
%inplace %install_default_config %install_profiles %load_ext %loadpy %logoff %logon  
%logstart %logstate %logstop %lsmagic %macro %magic %notebook %page %paste  
%pastebin %pdb %pdef %pdoc %pfile %pinfo %pinfo2 %pm %pop_err %pop_print %popd  
%pprint %precision %print_methods %print_traits %profile %prun %psearch %psource %pt  
%push_err %push_print %pushd %pwd %pycat %pylab %quickref %recall %rehashx  
%reload_ext %rep %replace_context %rerun %reset %reset_selective %run %run_examples  
%save %sc %store %sx %sym %tb %time %timeit %unalias %unload_ext %who %who_ls  
%whos %xdel %xmode
```



Read simple Tracebacks

```
>>> 100 + "Hello world!"
```

```
-----  
TypeError          Traceback (most recent call last)  
/Users/mk/<ipython-input-7-3d139ed9b46e> in <module>()  
----> 1 100 + "Hello world!"  
TypeError: unsupported operand type(s) for +: 'int' and 'str'
```

```
>>> undevined_variable + 1
```

```
-----  
NameError          Traceback (most recent call last)  
/Users/mk/<ipython-input-8-8514a074ce6b> in <module>()  
----> 1 undevined_variable + 1  
NameError: name 'undevined_variable' is not defined
```



Interactive Calculator

```
# adding two values
```

```
>>> 5 + 10
```

```
15
```

```
# setting a variable
```

```
>>> a = 5
```

```
>>> a
```

```
5
```

```
# checking the variable's type
```

```
>>> type(a)
```

```
int
```

```
# an arbitrary long integer
```

```
>>> a = 12345678901234567890
```

```
>>> a
```

```
12345678901234567890L
```

```
>>> type(a)
```

```
long
```

```
# remove 'a' from the 'namespace'
```

```
>>> del a
```

```
>>> a
```

```
NameError Traceback (most recent call last)
```

```
/Users/mk/<ipython-input-27-60b725f10c9c>
```

```
in <module>()
```

```
----> 1 a
```

```
NameError: name 'a' is not defined
```



Interactive Calculator

```
# real numbers
```

```
>>> b = 1.4 + 2.3
```

```
>>> b
```

```
3.699999999999997
```

```
# "prettier" version
```

```
>>> print b
```

```
3.7
```

```
>>> type(b)
```

```
float
```

```
# complex numbers
```

```
c = 5+5.5j
```


```
>>> c
```

```
(5+5.5j)
```



Variable declaration and initialization


Matlab/Python



`a = 'hello world'`

`a = 5.56`

C/C++/Java



~~`a = "hello world"`~~
~~`a = 5.5`~~

`float b = 5.5`
`std::string text= "Hello world" (C++)`



Interactive Calculator

arithmetic operations

```
>>> 1+2-(3*4/6)**5+(7%2)  
-27
```

simple math functions

```
>>> abs(-6e3)  
6000.0  
  
>>> max(0, min(10, -1, 4, 3))  
0  
  
>>> round(2.71235897456)  
3.0
```

Python math functions:

<http://docs.python.org/library/math.html>

casting

```
>>> int(2.718281828)  
2  
  
>>> float(2)  
2.0  
  
>>> 1 + 2.  
3.0  
  
>>> int('456')  
456  
  
>>> str(65)  
'65' ← string
```

in place operations +=, -=, *=, /=, etc.

```
>>> b = 2.5  
  
>>> b+=0.5 # b = b+5  
  
>>> b
```



Definition of function



Exercise



Homework